

File Copy

NOAA Technical Memorandum NOS NGS-25



REVISIONS OF THE HOACOS HEIGHT-CONTROLLED
NETWORK ADJUSTMENT PROGRAM

National Geodetic Survey
Rockville, Md.
May 1980

**U.S. DEPARTMENT OF
COMMERCE**

National Oceanic and
Atmospheric Administration

National Ocean
Survey

NOAA Technical Publications

National Ocean Survey/National Geodetic Survey subseries

The National Geodetic Survey (NGS) of the National Ocean Survey (NOS), NOAA, establishes and maintains the basic National horizontal and vertical networks of geodetic control and provides governmentwide leadership in the improvement of geodetic surveying methods and instrumentation, coordinates operations to assure network development, and provides specifications and criteria for survey operations by Federal, State, and other agencies.

NGS engages in research and development for the improvement of knowledge of the figure of the Earth and its gravity field, and has the responsibility to procure geodetic data from all sources, process these data, and make them generally available to users through a central data base.

NOAA Technical Memorandums and some special NOAA publications are sold by the National Technical Information Service (NTIS) in paper copy and microfiche. Orders should be directed to NTIS, 5285 Port Royal Road, Springfield, VA 22161 (telephone: 703-557-4650). NTIS customer charge accounts are invited; some commercial charge accounts are accepted. When ordering, give the NTIS accession number (which begins with PB) shown in parentheses in the following citations.

Paper copies of NOAA Technical Reports, that are of general interest to the public, are sold by the Superintendent of Documents, U.S. Government Printing Office (GPO), Washington, DC 20402 (telephone: 202-783-3238). For prompt service, please furnish the GPO stock number with your order. If a citation does not carry this number, then the publication is not sold by GPO. All NOAA Technical Reports may be purchased from NTIS in hard copy and microform. Prices for the same publication may vary between the two Government sales agents. Although both are nonprofit, GPO relies on some Federal support whereas NTIS is self-sustained.

An excellent reference source for Government publications is the National Depository Library program, a network of about 1,300 designated libraries. Requests for borrowing Depository Library material may be made through your local library. A free listing of libraries currently in this system is available from the Library Division, U.S. Government Printing Office, 5236 Eisenhower Ave., Alexandria, VA 22304 (telephone: 703-557-9013).

NOAA geodetic publications

Classification, Standards of Accuracy, and General Specifications of Geodetic Control Surveys. Federal Geodetic Control Committee, John O. Phillips (Chairman), Department of Commerce, NOAA, NOS, 1974 reprinted annually, 12 pp (PB265442). National specifications and tables show the closures required and tolerances permitted for first-, second-, and third-order geodetic control surveys. (A single free copy can be obtained, upon request, from the National Geodetic Survey, OA/C18x2, NOS/NOAA, Rockville, MD 20852.)

Specifications To Support Classification, Standards of Accuracy, and General Specifications of Geodetic Control Surveys. Federal Geodetic Control Committee, John O. Phillips (Chairman), Department of Commerce, NOAA, NOS, 1975, reprinted annually, 30 pp (PB261037). This publication provides the rationale behind the original publication, "Classification, Standards of Accuracy, ..." cited above. (A single free copy can be obtained, upon request, from the National Geodetic Survey, OA/C18x2, NOS/NOAA, Rockville, MD 20852.)

Proceedings of the Second International Symposium on Problems Related to the Redefinition of North American Geodetic Networks. Sponsored by U.S. Department of Commerce; Department of Energy, Mines and Resources (Canada); and Danish Geodetic Institute; Arlington, Va., 1978, 658 pp. (GPO #003-017-0426-1). Fifty-four papers present the progress of the new adjustment of the North American Datum at mid-point, including reports by participating nations, software descriptions, and theoretical considerations.

NOAA Technical Memorandums, NOS/NGS subseries

- NOS NGS-1 Use of climatological and meteorological data in the planning and execution of National Geodetic Survey field operations. Robert J. Leffler, December 1975, 30 pp (PB249677). Availability, pertinence, uses, and procedures for using climatological and meteorological data are discussed as applicable to NGS field operations.
- NOS NGS-2 Final report on responses to geodetic data questionnaire. John F. Spencer, Jr., March 1976, 39 pp (PB254641). Responses (20%) to a geodetic data questionnaire, mailed to 36,000 U.S. land surveyors, are analyzed for projecting future geodetic data needs.

(Continued at end of publication)

NOAA Technical Memorandum NOS NGS-25

REVISIONS OF THE HOACOS HEIGHT-CONTROLLED
NETWORK ADJUSTMENT PROGRAM

T. Vincenty

National Geodetic Survey
Rockville, Md.
May 1980

UNITED STATES
DEPARTMENT OF COMMERCE
Philip M. Klutznick, Secretary

NATIONAL OCEANIC AND
ATMOSPHERIC ADMINISTRATION
Richard A. Frank, Administrator

National Ocean
Survey
Herbert R. Lippold, Jr., Director



CONTENTS

Abstract	1
1. Introduction	1
2. Adjustment in the Geodetic Horizon System	1
3. Stations Without Astronomic Coordinates	3
4. Stations Without Heights	4
5. Elimination of Station Orientation Unknowns	4
References	5

REVISIONS OF THE HOACOS HEIGHT-CONTROLLED
NETWORK ADJUSTMENT PROGRAM

T. Vincenty
National Geodetic Survey
National Ocean Survey, NOAA
Rockville, Md. 20852

ABSTRACT: The HOACOS height-controlled adjustment program has been revised in several places. Its new features include the adjustment in the geodetic horizon system, a change of units for compatibility with other programs, a revised method of treating the direction of gravity at stations with no astronomic data, and the handling of observations when some heights are not given.

1. INTRODUCTION

HOACOS is a computer program for adjusting horizontal networks in space with heights held fixed and without reducing observations to the surface of an ellipsoid. Experience with this program disclosed the need for certain revisions to make it more general in application. These revisions are described below, using the same notation as in the previous report (Vincenty 1979) unless otherwise shown.

2. ADJUSTMENT IN THE GEODETIC HORIZON SYSTEM

In the original version of HOACOS the coordinate unknowns were linear shifts in the plane of the astronomic horizon at each station and the shifted points were reduced to the constant height surface after the adjustment. This is the most efficient method, making it unnecessary to compute numerous trigonometric functions of geodetic parameters. However, this does not provide compatibility with programs of other agencies which express the unknowns in angular units such as seconds. This problem arises when reduced normal equations of two countries are to be combined in the Helmert-Wolf block adjustment method, in which case the unknowns of all partial systems must be expressed in the same units. Moreover, the linear shifts dx' , dy' in the astronomic horizon plane are not the same as the corresponding shifts dx , dy in the geodetic horizon; therefore, in order to ensure the desired compatibility, the shifts must first be expressed in the geodetic horizon system.

The azimuth and distance observation equations in the astronomic horizon system have the form

$$v = a_1 dx'_1 + a_2 dy'_1 + a_3 dx'_2 + a_4 dy'_2 + K. \quad (1)$$

For use with the geodetic horizon they are rewritten as

$$v = b_1 dx_1 + b_2 dy_1 + b_3 dx_2 + b_4 dy_2 + K. \quad (2)$$

To derive the coefficients of (2), the following rotation matrices are first defined:

$$R_a = \begin{bmatrix} -\sin \phi \cos \lambda & -\sin \phi \sin \lambda & \cos \phi \\ -\sin \lambda & \cos \lambda & 0 \\ \cos \phi \cos \lambda & \cos \phi \sin \lambda & \sin \phi \end{bmatrix} \quad (3)$$

$$R_g = \begin{bmatrix} -\sin B \cos L & -\sin B \sin L & \cos B \\ -\sin L & \cos L & 0 \\ \cos B \cos L & \cos B \sin L & \sin B \end{bmatrix} \cdot \quad (4)$$

The shifts in the astronomic and geodetic horizon systems are related by

$$[dx, dy, dH]^T = R_g R_a^T [dx', dy', dH']^T. \quad (5)$$

An evaluation of (5) with the usual second-order approximations gives

$$\begin{bmatrix} dx \\ dy \\ dH \end{bmatrix} = \begin{bmatrix} 1 & \sin \phi (\lambda - L) & (\phi - B) \\ -\sin \phi (\lambda - L) & 1 & \cos \phi (\lambda - L) \\ -(\phi - B) & -\cos \phi (\lambda - L) & 1 \end{bmatrix} \begin{bmatrix} dx' \\ dy' \\ dH' \end{bmatrix} \cdot \quad (6)$$

In eq. (6), $\lambda - L$ is an approximation of $\sin (\lambda - L)$ which can be written as

$$\sin (\lambda - L) = (X \sin \lambda - Y \cos \lambda)/p \quad (7)$$

where $p = \sqrt{X^2 + Y^2}$. This leads to the following coefficients for use with eq. (2):

$$\begin{aligned} b_1 &= a_1 + m_1 a_2 & b_3 &= a_3 + m_2 a_4 \\ b_2 &= a_2 - m_1 a_1 & b_4 &= a_4 - m_2 a_3 \end{aligned} \quad (8)$$

in which

$$m_1 = \sin \phi_1 (X_1 \sin \lambda_1 - Y_1 \cos \lambda_1)/p_1 \quad (9)$$

$$m_2 = \sin \phi_2 (X_2 \sin \lambda_2 - Y_2 \cos \lambda_2)/p_2 \cdot \quad (10)$$

Let $M' = M + H$ and $N' = (N + H) \cos B = p$. Then the observation equation for an astronomic azimuth, with the shifts dB , dL and the constant term expressed in seconds, becomes

$$v = b_1 M'_1 dB_1 + b_2 N'_1 dL_1 + b_3 M'_2 dB_2 + b_4 N'_2 dL_2 + K \quad (11)$$

and the observation equation for a distance, with K in linear units, becomes

$$v = \text{arc } 1''(b_1 M'_1 dB_1 + b_2 N'_1 dL_1 + b_3 M'_2 dB_2 + b_4 N'_2 dL_2) + K. \quad (12)$$

The radii of curvature M and N are needed to five or six figures but they are computed in the program to much better precision. For this purpose a rapid formula is used to obtain $\tan B$:

$$\tan B = \frac{Z(a + H)^2}{p(b + H)^2} \quad (13)$$

where a and b are major and minor semiaxes of the ellipsoid. Eq. (13) is an approximation of

$$\tan B = \frac{Z(a + H)^2}{p(b + H)^2} \left[1 + \frac{1}{4} e^4 H(Z^2 - p^2)/a^3 \right] \quad (14)$$

(Vincenty 1980), in which the elliptic term amounts to at most $0.0001''$ per 1000 meters of H in all terrestrial applications.

3. STATIONS WITHOUT ASTRONOMIC COORDINATES

Theory requires that the direction of gravity be known at all stations from which directions are measured. This is seldom the case, therefore some approximate values must be used for astronomic coordinates. In the classical method of adjusting on the ellipsoid the implied assumption in such cases is that astronomic coordinates are the same as the corresponding most recent geodetic values. The original version of HOACOS assumed that they are the same as the first preliminary geodetic values. Neither approach is theoretically correct. In the present HOACOS version the sines and the cosines of such pseudo-astronomic coordinates are updated between iterations to correspond to geodetic values. This is accomplished by

$$d(\sin \phi) = \cos \phi dB \quad (15a)$$

$$d(\cos \phi) = -\sin \phi dB \quad (15b)$$

and similarly for $\sin \lambda$ and $\cos \lambda$. This approach does not improve the results of an adjustment (though it may change them slightly), but in the case when the astronomic coordinates have been derived from gravimetric deflections and from preliminary geodetic positions it automatically corrects the assumed direction of gravity for the change in geodetic position, as is necessary.

4. STATIONS WITHOUT HEIGHTS

In the practice employed by the National Geodetic Survey the heights of unoccupied intersection stations are not used in the adjustment. In the classical method of adjustment on an ellipsoid by the TRAV10 program (Schwarz 1978) the direction to such points do not receive deflection corrections nor skew normals corrections. In the height-controlled method on which HOACOS is based, these corrections are implicit. There may be cases when the standpoint is at an elevation of some thousands of meters. The forepoint, with no elevation given, is assumed to be at zero height. If, in addition, astrogeodetic deflections at the standpoint are large, the computed astronomic azimuth (and consequently also the adjusted direction) over this line could be wrong by tens of seconds because of the fictitious steepness of the line as defined by ΔX , ΔY , ΔZ values between these points. Some method is needed to nullify the errors caused by the assumption of zero height at the forepoint.

In such cases the elevated point is projected on the ellipsoid by

$$\delta X = -(X/p) H \cos B \quad (16a)$$

$$\delta Y = -(Y/p) H \cos B \quad (16b)$$

$$\delta Z = - H \sin B \quad (16c)$$

and the observation equation for this line is formed as if both points were at zero height. The coefficients of dx_1 and dy_1 are multiplied by

$$F = a/(a + H) . \quad (17)$$

A similar situation occurs when a direction and a sea level distance are given over a short line, normally within 100 meters, and the height of one of the stations is missing. Then the same procedure is used as in the case of a direction to an intersection station.

5. ELIMINATION OF STATION ORIENTATION UNKNOWNNS

A separate version of HOACOS was created in which station orientation unknownns are eliminated by the well-known Schreiber method. It has not yet been determined whether the elimination of these unknownns is profitable. One disadvantage of this method is that it does not give directly the standard errors of the eliminated unknownns which are needed for the computation of the tau statistics to flag observations for possible rejections (Pope 1976).

REFERENCES

- Pope, A. J., 1976: The statistics of residuals and the detection of outliers. NOAA Technical Report NOS 65 NGS-1, 133 pp.
- Schwarz, C. R., 1978: TRAV10 horizontal network adjustment program. NOAA Technical Memorandum NOS NGS-12, 52 pp.
- Vincenty, T., 1979: HOACOS - A program for adjusting horizontal networks in three dimensions. NOAA Technical Memorandum NOS NGS-19, 13 pp.
- Vincenty, T., 1980: Zur räumlich-ellipsoidischen Koordinaten-Transformation. Zeitschrift für Vermessungswesen (in press).

(Continued from inside front cover)

- NOS NGS-3 Adjustment of geodetic field data using a sequential method. Marvin C. Whiting and Allen J. Pope, March 1976, 11 pp (PB253967). A sequential adjustment is adopted for use by NGS field parties.
- NOS NGS-4 Reducing the profile of sparse symmetric matrices. Richard A. Snay, June 1976, 24 pp (PB-258476). An algorithm for improving the profile of a sparse symmetric matrix is introduced and tested against the widely used reverse Cuthill-McKee algorithm.
- NOS NGS-5 National Geodetic Survey data: availability, explanation, and application. Joseph F. Dracup, Revised January 1979, 45 pp (PB80 118615). The summary gives data and services available from NGS, accuracy of surveys, and uses of specific data.
- NOS NGS-6 Determination of North American Datum 1983 coordinates of map corners. T. Vincenty, October 1976, 8 pp (PB262442). Predictions of changes in coordinates of map corners are detailed.
- NOS NGS-7 Recent elevation change in Southern California. S.R. Holdahl, February 1977, 19 pp (PB265-940). Velocities of elevation change were determined from Southern Calif. leveling data for 1906-62 and 1959-76 epochs.
- NOS NGS-8 Establishment of calibration base lines. Joseph F. Dracup, Charles J. Fronczek, and Raymond W. Tomlinson, August 1977, 22 pp (PB277130). Specifications are given for establishing calibration base lines.
- NOS NGS-9 National Geodetic Survey publications on surveying and geodesy 1976. September 1977, 17 pp (PB275181). Compilation lists publications authored by NGS staff in 1976, source availability for out-of-print Coast and Geodetic Survey publications, and subscription information on the Geodetic Control Data Automatic Mailing List.
- NOS NGS-10 Use of calibration base lines. Charles J. Fronczek, December 1977, 38 pp (PB279574). Detailed explanation allows the user to evaluate electromagnetic distance measuring instruments.
- NOS NGS-11 Applicability of array algebra. Richard A. Snay, February 1978, 22 pp (PB281196). Conditions required for the transformation from matrix equations into computationally more efficient array equations are considered.
- NOS NGS-12 The TRAV-10 horizontal network adjustment program. Charles R. Schwarz, April 1978, 52 pp (PB283087). The design, objectives, and specifications of the horizontal control adjustment program are presented.
- NOS NGS-13 Application of three-dimensional geodesy to adjustments of horizontal networks. T. Vincenty and B. R. Bowring, June 1978, 7 pp (PB286672). A method is given for adjusting measurements in three-dimensional space without reducing them to any computational surface.
- NOS NGS-14 Solvability analysis of geodetic networks using logical geometry. Richard A. Snay, October 1978, 29 pp (PB291286). No algorithm based solely on logical geometry has been found that can unerringly distinguish between solvable and unsolvable horizontal networks. For leveling networks such an algorithm is well known.
- NOS NGS-15 Goldstone validation survey - phase 1. William E. Carter and James E. Pettey, November 1978, 44 pp (PB292310). Results are given for a space system validation study conducted at the Goldstone, Calif., Deep Space Communication Complex.
- NOS NGS-16 Determination of North American Datum 1983 coordinates of map corners (second prediction). T. Vincenty, April 1979, 6 pp (PB297245). New predictions of changes in coordinates of map corners are given.
- NOS NGS-17 The HAVAGO three-dimensional adjustment program. T. Vincenty, May 1979, 18 pp (PB297069). The HAVAGO computer program adjusts numerous kinds of geodetic observations for high precision special surveys and ordinary surveys.
- NOS NGS-18 Determination of astronomic positions for California-Nevada boundary monuments near Lake Tahoe. James E. Pettey, March, 1979, 22 pp (PB301264). Astronomic observations of the 120th meridian were made at the request of the Calif. State Lands Commission.
- NOS NGS-19 HOACOS: A program for adjusting horizontal networks in three dimensions. T. Vincenty, July 1979, 18 pp (PB301351). Horizontal networks are adjusted simply and efficiently in the height-controlled spatial system without reducing observations to the ellipsoid.
- NOS NGS-20 Geodetic leveling and the sea level slope along the California coast. Emery I. Balazs and Bruce C. Douglas, September 1979, 23 pp (PB80 120611). Heights of four local mean sea levels for the 1941-59 epoch in California are determined and compared from five geodetic level lines observed (leveled) between 1968-78.
- NOS NGS-21 Haystack-Westford Survey. W. E. Carter, C. J. Fronczek, and J. E. Pettey, September 1979, 57 pp. A special purpose survey was conducted for VLBI test comparison.
- NOS NGS-22 Gravimetric tidal loading computed from integrated Green's functions. C. C. Goad, October 1979, 15 pp. Tidal loading is computed using integrated Green's functions.
- NOS NGS-23 Use of auxiliary ellipsoids in height-controlled spatial adjustments. B. R. Bowring and T. Vincenty, November 1979, 6 pp. Auxiliary ellipsoids are used in adjustments of networks in the height-controlled three-dimensional system for controlling heights and simplifying transformation of coordinates.
- NOS NGS-24 Determination of the geopotential from satellite-to-satellite tracking data. B. C. Douglas, C. C. Goad, and F. F. Morrison, January 1980, 32 pp. The capability of determining the geopotential from satellite-to-satellite tracking is analyzed.

(Continued on inside back cover)

(Continued)

NOAA Technical Reports, NOS/NGS subseries

- NOS 65 NGS 1 The statistics of residuals and the detection of outliers. Allen J. Pope, May 1976, 133 pp (PB258428). A criterion for rejection of bad geodetic data is derived on the basis of residuals from a simultaneous least-squares adjustment. Subroutine TAURE is included.
- NOS 66 NGS 2 Effect of Geociever observations upon the classical triangulation network. R. E. Moose and S. W. Henriksen, June 1976, 65 pp (PB260921). The use of Geociever observations is investigated as a means of improving triangulation network adjustment results.
- NOS 67 NGS 3 Algorithms for computing the geopotential using a simple-layer density model. Foster Morrison, March 1977, 41 pp (PB266967). Several algorithms are developed for computing with high accuracy the gravitational attraction of a simple-density layer at arbitrary altitudes. Computer program is included.
- NOS 68 NGS 4 Test results of first-order class III leveling. Charles T. Whalen and Emery Balazs, November 1976, 30 pp (GPO# 003-017-00393-1) (PB265421). Specifications for releveling the National vertical control net were tested and the results published.
- NOS 70 NGS 5 Selenocentric geodetic reference system. Frederick J. Doyle, Atef A. Elassal, and James R. Lucas, February 1977, 53 pp (PB266046). Reference system was established by simultaneous adjustment of 1,233 metric-camera photographs of the lunar surface from which 2,662 terrain points were positioned.
- NOS 71 NGS 6 Application of digital filtering to satellite geodesy. C. C. Goad, May 1977, 73 pp (PB-270192). Variations in the orbit of GEOS-3 were analyzed for M_2 tidal harmonic coefficient values that perturb the orbits of artificial satellites and the Moon.
- NOS 72 NGS 7 Systems for the determination of polar motion. Soren W. Henriksen, May 1977, 55 pp (PB274698). Methods for determining polar motion are described and their advantages and disadvantages compared.
- NOS 73 NGS 8 Control leveling. Charles T. Whalen, May 1978, 23 pp (GPO# 003-017-00422-8) (PB286838). The history of the National network of geodetic control, from its origin in 1878, is presented in addition to the latest observational and computational procedures.
- NOS 74 NGS 9 Survey of the McDonald Observatory radial line scheme by relative lateration techniques. William E. Carter and T. Vincenty, June 1978, 33 pp (PB287427). Results of experimental application of the "ratio method" of electromagnetic distance measurements are given for high resolution crustal deformation studies in the vicinity of the McDonald Lunar Laser Ranging and Harvard Radio Astronomy Stations.
- NOS 75 NGS 10 An algorithm to compute the eigenvectors of a symmetric matrix. E. Schmid, August 1978, 5 pp (PB287923). Method describes computations for eigenvalues and eigenvectors of a symmetric matrix.
- NOS 76 NGS 11 The application of multiquadric equations and point mass anomaly models to crustal movement studies. Rolland L. Hardy, November 1978, 63 pp (PB293544). Multiquadric equations, both harmonic and nonharmonic, are suitable as geometric prediction functions for surface deformation and have potentiality for usage in analysis of subsurface mass redistribution associated with crustal movements.
- NOS 79 NGS 12 Optimization of horizontal control networks by nonlinear programming. Dennis G. Milbert, August 1979, 44 pp (PB80 117948). Several horizontal geodetic control networks are optimized at minimum cost while maintaining desired accuracy standards.
- NOS 82 NGS 13 Feasibility study of the conjugate gradient method for solving large sparse equation sets. Lothar Grundig, February 1980, 22 pp. Method is suitable for constrained adjustments of triangulation networks but not for free adjustments.
- NOS 83 NGS 14 Tidal corrections to geodetic quantities. Peter Vanicek, February 1980, 30 pp. Corrections for tidal force are formulated and tidal aspects relating to geodesy are discussed.
- NOS 84 NGS 15 Application of special variance estimators to geodesy. John D. Bossler and Robert H. Hanson, February 1980. Special variance estimators, one involving the use of noninteger degrees of freedom, are analyzed and applied to least-square adjustments of geodetic control networks to determine their effectiveness.
- NOS 85 NGS 16 The Bruns transformation and a dual setup of geodetic observational equations. Erik W. Grafarend, April 1980, 73 pp. Geometric and physical observations are combined within a unified theoretical framework.

NOAA Manuals, NOS/NGS subseries

- NOS NGS 1 Geodetic bench marks. Lt. Richard P. Floyd, September 1978, 56 pp (GPO# 003-017-00442-2) (PB296427). Reference guide provides specifications for highly stable bench marks, including chapters on installation procedures, vertical instability, and site selection considerations.

U.S. DEPARTMENT OF COMMERCE
National Oceanic and Atmospheric Administration
National Ocean Survey
National Geodetic Survey, C18x2
Rockville, Maryland 20852

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
U.S. DEPARTMENT OF COMMERCE
COM-210
THIRD CLASS MAIL



NOAA--S/T 80-168