

# Block CS05 (Central South 05)

---

*GRAV-D Airborne Data Release User Manual*

*Applies to Data BETA Release, 9/2014*

Edited by Monica A. Youngman, Carly A. Weil and Timothy Salisbury

## Introduction to GRAV-D and Data User Manuals

NOAA's National Geodetic Survey (NGS) launched the Gravity for the Redefinition of the American Vertical Datum (GRAV-D) program in 2007. This program is designed to replace the current national vertical datum (NAVD 88) with a datum based upon a gravimetric geoid by 2022. To produce the geoid with 1-2 cm accuracy (where possible), an airborne campaign has been launched to measure the gravity field over all of the US and its holdings.

A more comprehensive description of the GRAV-D project is available in the "GRAV-D General Airborne Gravity Data User Manual." The version of that manual that applies to this release is manual v. 2.X. That manual also describes general details of the nominal airborne field operations, data post-processing software specifics, data naming schemes and distribution, data formats, and how to calculate other commonly-used gravity values from the released data. This manual relates details for this block of data that are in addition to the General User Manual.

GRAV-D uses some specific terminology (e.g. "block" for a geographic area with enough flown data and tie lines to provide error statistics, and "survey" for an occupation by the field team of a particular airport, at a particular time, and with a particular aircraft and instrument suite). For a full list of terminology, refer to the Glossary in the Appendices of the "GRAV-D General Airborne Gravity Data User Manual."

## Contents

Introduction to GRAV-D and Data User Manuals .....	1
Figure List .....	3
Table List .....	3
1. Block Description .....	4
2. Survey Design and Execution .....	5
2.1 GPS/IMU Instrumentation .....	7
2.2 Gravity Instrumentation .....	7
3. GPS and Gravity Data Processing .....	8
3.1 Whole-Survey Applicable Details .....	8
3.1.1 GPS .....	8
3.1.2 Ground Gravity Tie .....	8
3.1.3 Gravity Filtering .....	8
3.2 Whole-Block Applicable Details .....	9
3.2.1 Gravity Error Analysis .....	9
3.3 Flight- and Line-Specific Details .....	11
3.3.1 GPS processing- by flight .....	11
3.3.2 Gravity processing- by line .....	12
4. Data Usage Guidelines .....	18
4.1 Suggested Data Handling .....	18
4.2 Documentation .....	18
4.3 How to Cite These Data .....	18
5. References .....	18

## Figure List

Figure 1: Google Earth Image of the Location of Block CS05 .....	4
Figure 2: Data Coverage for CS05.....	6
Figure 3: Crossover Residuals, Histogram, and Statistics for Block CS05. ....	10
Figure 4: Full-field gravity at altitude (mean removed) for Block CS05.....	16
Figure 5: Free-air gravity disturbance for Block CS05 with respect to the WGS-84 ellipsoid...17	

## Table List

Table 1: Latitude and Longitude Coordinates of Corner Points Defining Block CS05 .....	4
Table 2: Survey Overview .....	5
Table 3: Aircraft and Instrumentation.....	5
Table 4: Survey Design and Execution.....	5
Table 5: Lever Arm Measurements FROM the Center of the Gravimeter's Sensor TO the Other Instruments.....	7
Table 6: Lever Arm Measurements FROM the SPAN TO the GPS Antenna .....	7
Table 7: GPS High Rate Data Availability (1 Hz or higher).....	8
Table 8: Gravity Crossover Error Analysis .....	9
Table 9: Quality of Cross Lines Used in Crossover Analysis.....	11
Table 10: Average Data Line Correlation.....	11
Table 11: GPS+IMU and GPS-only Kinematic Processing Results.....	13
Table 12: Gravity Processing Results.....	14
Table 13: Bias from EGM08 by Line .....	15

## 1. Block Description

GRAV-D Block **CS05** is located in the **C**entral Time Zone, in the **S**outh half (south of 40° latitude). This was the fifth (**05**) block of data completed in that region. Block CS05 is about 550 km by 330 km over southern Texas overlapping into Mexico ([Figure 1](#)). The corner coordinates defining Block CS05 are listed in [Table 1](#).



Figure 1: Google Earth Image of the Location of Block CS05.

Table 1: Latitude and Longitude Coordinates of Corner Points Defining Block CS05

Latitude (decimal degrees)	Longitude (decimal degrees)
30.042508452	-101.991631149
27.638084869	-101.987492235
24.971412205	-99.9761499902
25.066796481	-98.2841017513
30.018616787	-98.6413583420

## 2. Survey Design and Execution

Airborne gravity data in Block CS05 were collected during two surveys: TX14-1 (Texas 2014, first occupation) & TX14-2 (TX 2014, second occupation). All data and cross flights were done at 20,000 ft.. [Table 2](#), [Table 3](#), and [Table 4](#) give a synopsis of survey layout and execution for the data. [Figure 2](#) shows the data coverage, plotted in Google Earth.

In the CS05 all data lines are North-South and cross lines East-West. The block consists of 37 data lines, 7 cross lines. In the data file, line numbers are preceded by the block name (i.e. CS05101= block CS05's line 101).

*Table 2: Survey Overview*

Conducting Organization	NOAA- National Geodetic Survey	
Survey Name	TX14-1	TX14-2
Airport Base of Operations	Austin-Bergstrom Airport (KAUS) 3600 Presidential Boulevard Austin, TX 78719	Preston Smith Intl' Airport (KLBB) Lubbock Aero FBO 6304 N. Cedar Avenue. Lubbock, TX 79403
Geographic Location	Southern Texas, Northern Coahuila (Mexico)	
Dates of Airborne Operations	Jan 6 <sup>th</sup> -March 2nd 2014	Sept 12 <sup>th</sup> -Nov 26 <sup>th</sup> 2014

*Table 3: Aircraft and Instrumentation*

Aircraft	Alaska Fire Service (BLM) Pilatus PC-12	
Engines, number and type	1, Turboprop	
Gravity Instrumentation	Micro-g LaCoste (MGL) TAGS S-161 (relative) MGL A-10 25 (absolute) MGL D-43, G-6 (relative)	Micro-g LaCoste (MGL) TAGS S-137 (relative) MGL A-10 25 (absolute) MGL D-43, G-6 (relative)
GPS Instrumentation	NovAtel DL-4 Plus NovAtel SPAN-SE (GPS + IMU)	

*Table 4: Survey Design and Execution*

Line Spacing	Data Lines: 10 km Cross Lines: ~40 km
Type of Layout	Regular data lines & regular cross lines
Nominal Survey Altitude	20,000
Nominal Aircraft Ground Speed	250 knots
Number of Lines Released	Data Lines: 37 Cross Lines: 7 Repeat Lines: 0
Number of Crossovers	210






Figure 2: Data Coverage for CS05. Data lines start in the east at 101 and continue west to 134. Airports marked with red and blue stars.

## 2.1 GPS/IMU Instrumentation

The Pilatus PC-12 had one GPS antennas available for scientific measurements. Two geodetic-quality GPS receivers shared the antenna: NovAtel DL-4 Plus (included as part of the TAGS gravimeter timing unit) and a NovAtel (inside the SPAN-SE system). The NovAtels had a data rate of 1 Hz and the SPAN NovAtel of 20Hz. The NovAtel  $\mu$ IMU system also contained an Inertial Measurement Unit (IMU) that recorded aircraft orientation information at 200 Hz during the flight, including pitch, roll, yaw, and heading.

On the ground, two Ashtech Z-Surveyors recorded at 1 Hz and served as GPS base stations throughout the survey. See Section [3.2.1](#) for a table of GPS data available for each flight and processing details.

## 2.2 Gravity Instrumentation

The Micro-g LaCoste TAGS (Turn-key Airborne Gravimetry System) was mounted in the cargo area. The TAGS records data at 1Hz and has a NovAtel timing unit mounted on the gravimeter. The gravimeter also records an environmental file at 0.1 Hz. For more information on the instrument, refer to its user manual (Micro-g LaCoste, 2010).

The IMU was mounted on top of the TAGS and in the center of the frame. [Table 5](#) lists the lever arm measurements between the TAGS and other instruments (distances are measured along the body of the aircraft: X positive toward the nose, Y positive toward the right, and Z positive down.) [Table 6](#) lists the lever arm measurement between the TAGS and the SPAN-SE (distances measured along the body of the aircraft: X positive toward the right, Y positive toward the nose, and Z positive up).

*Table 5: Lever Arm Measurements FROM the Center of the Gravimeter's Sensor TO the Other Instruments*

TX14

Instrument/Location	X (m)	Y (m)	Z (m)
NovAtel SPAN-SE IMU (TX14-1)	-0.017	0.019	-0.433
NovAtel SPAN-SE IMU (TX14-2)	0.150	0.100	-0.410

*Table 6: Lever Arm Measurements FROM the SPAN TO the GPS Antenna*

Instrument/Location	X (m)	Y (m)	Z (m)
GPS Antenna	-0.008	0.669	0.615

## 3. GPS and Gravity Data Processing

### 3.1 Whole-Survey Applicable Details

#### 3.1.1 GPS

Table 7: GPS High Rate Data Availability (1 Hz or higher)

Airport	Type	Receiver	Flight Available	2014 Day of Year Available
KAUS	Kinematic	NovAtel (0008)	F01-F04, F06-F23	19, 22, 25-26, 37, 39-40, 43, 46-48, 50-54, 58-60
		NovAtel (SPAN)	F01-F04, F06-F23	19, 22, 25-26, 37, 39-40, 43, 46-48, 50-54, 58-60
	Static	Ashtech NOTH	F01-F04, F06-F23	19, 22, 25-26, 37, 39-40, 43, 46-48, 50-54, 58-60
		Ashtech SOTH	F01-F04, F06-F23	19, 22, 25-26, 37, 39-40, 43, 46-48, 50-54, 58-60
KLBB	Kinematic	NovAtel (0009)	F05	299
		NovAtel (SPAN)	F05	299
	Static	Ashtech NOTH	F05	299
		Ashtech SOTH	F05	299

Data were processed using WGS84 and ITRF08. Average position accuracy for the data block is calculated from the final GPS position solution. Position standard deviation is estimated by the GPS processing programs for each flight and those numbers are averaged to provide a survey-wide estimate of GPS position accuracy. For the data lines, the average horizontal position accuracy is 0.0107 m and the average vertical position accuracy is 0.006 m.

#### 3.1.2 Ground Gravity Tie

Absolute gravity measurements were performed by NGS with a Micro-g LaCoste A-10 gravimeter in July 2013. The A-10 was set up at the exact location of the aircraft. The positions were determined from the GPS collected during the gravity survey while the plane was parked. In Austin, TX the location is designated as AUS TAGS (30.183921115°N , -97.6620560917°W) and it has an absolute gravity value of  $979273.7310 \pm 0.00801$  at 120.8 cm above the tarmac. In Lubbock, TX the location is designated as KLBB TAGS (33.644480033°N , -101.836436513°W) and it has an absolute gravity value of  $979307.8547 \pm 0.01166$  mGal at 163.7 cm above the tarmac.

#### 3.1.3 Gravity Filtering

Newton v1.2 uses a time-domain Gaussian filter that is applied three times to the data during final filtering. The Gaussian filter chosen for this survey has a 6-sigma of 120s, i.e. a 2-sigma of only 40s. Applying the filter three times provides superior noise reduction compared to a single application of the filter. Although the triple application provides better noise reduction, the filter is tailored to best preserve the amplitudes of the long wavelength signal, while allowing some short wavelength noise to remain in the final product. For suggestions on data handling, including on further noise suppression, see Section [4.1 Suggested Data Handling](#).



## 3.2 Whole-Block Applicable Details

### 3.2.1 Gravity Error Analysis

Crossover error analysis was done by identifying the crossing points of the data lines and cross lines and then applying the standard free-air correction to bring all points to the average altitude of the block. There was an unidentified bias in all flight lines, so an additional correction was applied before the crossover analysis to adjust each line's median airborne gravity value to the median gravity value of EGM08 along the line. The bias-corrected difference between the cross line gravity value and data line gravity value is the residual. The square root of the RMS of the residuals yields the total RMS error. For CS05, the result of the crossover analysis is shown in [Table 8](#) and in [Figure 3](#).

*Table 8: Gravity Crossover Error Analysis*

Nominal Altitude (ft)	Nominal Altitude (m)	Altitude for Analysis (m)	Number of Crossovers	RMS Of Residuals (mGal)	Std. Dev. Of Residuals (mGal)	Mean Crossover Difference (mgal)	RMS Error (mGal)
20,000	6,096	2,421	207	2.26	2.17	-0.67	1.60

One assumption of crossover analysis is that the quality of the cross lines are high and that the crossover difference reflects only the error in the data lines. This is not necessarily the case. This means that the crossover statistics do not accurately reflect the quality of the data lines, due to the errors in the cross lines. One way to quantify this problem is by reporting the standard deviation and mean of the crossover residuals for each cross line, as in [Table 9](#). The higher the standard deviation of the residuals, the more likely that the cross line was noisy. Also, a non-zero mean could indicate a cross-line bias with respect to the data lines (unlikely here because of the bias correction applied), which would produce false crossover statistics that indicate poor data line quality.




Figure 3: Crossover Residuals, Histogram, and Statistics for Block CS05. Color scale in mGals.

*Table 9: Quality of Cross Lines Used in Crossover Analysis*

Cross Line Number	Standard Deviation of Residuals Along Line (mGal)	Mean of Residuals Along Line (mGal)
601	2.62	-0.01
503	2.09	-0.22
504	1.31	-2.30
505	1.86	0.01
506	1.84	-1.47
507	2.37	0.90
551	1.39	-1.17

Another way to evaluate the quality of gravity data is to calculate the correlation of the gravity values along two adjacent data lines. Average correlation and statistics on the spread of correlations can yield information about the quality of the data lines ([Table 10](#)). This technique works well as a measure of data quality in areas with little lateral variability in the gravity field (such as the Gulf of Mexico). But the technique doesn't work well when the correlations are not expected to be high, such as in areas with large changes in topography and/or density from data line to data line. Line correlations were calculated for adjacent lines and then averaged to give an overall quality measurement. Correlations > 80% mean the lines are very highly correlated, 70% - 80% mean the lines are highly correlated, 50% - 70% mean the lines are more correlated than not, and <50% are more uncorrelated than correlated.

*Table 10: Average Data Line Correlation*

Number of Correlations	Average Data Line Correlation	Standard Deviation of Correlations
31	99.74%	0.78%

A fourth way of gauging data quality is by calculating the repeatability of the gravity signal along reflight lines of good quality. Reflight analysis can also help to pinpoint the lightest filtering that produces highly-correlated results.

### 3.3 Flight- and Line-Specific Details

#### 3.3.1 GPS processing- by flight

GPS data were processed in Inertial Explorer (IE) 8.5. A lever arm correction (to move the position solution from that of the GPS antenna to that of the center of the gravimeter) was applied within the IE software and included in the GPS+IMU solution. In the case of the GPS-only solution, no IMU data were available and a translation-only, vertical lever arm correction was instead applied by the Newton gravity code to translate the GPS-only positions to the center of the gravimeter.

NGS has developed an independent method of measuring the quality of GPS position solutions based on information available from IE. For the GPS-only part of the position solution, the quality analysis takes into account the following: whether a fixed or float solution was achieved, the magnitude of the combined separation between forward and reverse solutions (a measure

of precision), and the estimated position accuracy. For details on the calculation, please refer to the “GRAV-D General Airborne Gravity Data User Manual.”

### **3.3.2 Gravity processing- by line**

All gravity processing was done with NGS’ Newton v1.2 software. For a description of the package, refer to the “GRAV-D General Airborne Gravity Data User Manual.” The final gravity data file contains full-field gravity at altitude ([Figure 4](#)), although other gravity products such as free-air anomalies or free-air disturbances ([Figure 5](#)) can be easily calculated by following directions in Section 4 of the “GRAV-D General Airborne Gravity Data User Manual”.



Table 11: GPS+IMU and GPS-only Kinematic Processing Results

Survey	Flight Num.	Rover GPS Unit	Solution Type	Elevation Mask (degrees)	Line Num.	NGS Quality Grade
TX14-1	1	SPAN	GPS+IMU	7.5	601	100.00
	2	SPAN	GPS+IMU	5	101	89.13
					102	100.00
					201	100.00
	3	SPAN	GPS+IMU	7.5	103	99.69
					104	100.00
	4	SPAN	GPS+IMU	7.5	105	100.00
					106	100.00
					301	100.00
	6	SPAN	GPS+IMU	5	110	100.00
					209	100.00
	7	SPAN	GPS+IMU	5	111	100.00
					112	100.00
	8	SPAN	GPS+IMU	7.5	107	100.00
					108	100.00
	9	SPAN	GPS+IMU	7.5	123	100.00
					124	100.00
	10	SPAN	GPS+IMU	7.5	113	100.00
					114	100.00
	11	SPAN	GPS+IMU	7.5	115	100.00
					116	96.80
	12	SPAN	GPS+IMU	7.5	117	100.00
					118	100.00
	13	SPAN	GPS+IMU	7.5	119	100.00
					120	100.00
	14	SPAN	GPS+IMU	5	121	100.00
					122	100.00
	15	SPAN	GPS+IMU	5	125	100.00
					126	100.00
	16	SPAN	GPS+IMU	7.5	507	100.00
	17	SPAN	GPS+IMU	5	127	100.00
					128	100.00
	18	SPAN	GPS+IMU	7.5	505	100.00
					506	100.00
	19	SPAN	GPS+IMU	5	503	97.22
					504	100.00
	20	SPAN	GPS+IMU	5	551	100.00
	21	SPAN	GPS+IMU	5	204	100.00
	22	SPAN	GPS+IMU	5	129	100.00
					130	100.00
	23	SPAN	GPS+IMU	7.5	131	100.00
					132	100.00
TX14-2	5	SPAN	GPS+IMU	7.5	133	94.70
					134	100.00

Table 12: Gravity Processing Results

Survey	Flight Num.	Line Num.	Times of Deleted Data Section(s)
TX14-1	1	601	
	2	101	
		102	
		201	
	3	103	66109-66393
		104	68914-69456
	4	105	
		106	
		301	
	6	110	
		209	
	7	111	
		112	
	8	107	
		108	
	9	123	
		124	
	10	113	
		114	
	11	115	75275-75662
		116	
	12	117	
		118	
	13	119	
		120	
	14	121	60540-61269
		122	
	15	125	
		126	
	16	507	
	17	127	
		128	
	18	505	
		506	
	19	503	
		504	
	20	551	
	21	204	
	22	129	
		130	
	23	131	
		132	
TX14-2	5	133	
		134	

Table 13: Bias from EGM08 by Line

Survey	Flight Num.	Line Num.	Bias From EGM08
TX14-1	1	601	1.89
	2	101	1.14
		102	1.21
		201	1.32
	3	103	1.43
		104	2.24
	4	105	1.15
		106	1.26
		301	1.97
	6	110	1.09
		209	0.46
	7	111	0.79
		112	2.28
	8	107	-0.32
		108	2.16
	9	123	2.73
		124	4.31
	10	113	0.60
		114	1.29
	11	115	2.52
		116	0.78
	12	117	1.28
		118	1.34
	13	119	0.60
		120	-0.22
	14	121	1.87
		122	1.22
	15	125	0.42
		126	0.64
	16	507	2.60
	17	127	1.69
		128	1.18
	18	505	1.18
		506	-1.01
	19	503	1.59
		504	-0.51
	20	551	-0.19
	21	204	0.30
	22	129	1.94
		130	1.18
	23	131	2.28
		132	1.18
TX14-2	5	133	
		134	




Figure 4: Full-field gravity at altitude (mean removed) for Block CS05. This is the data in the gravity release ".txt" file and includes the effects of differing altitudes along flight lines.






Figure 5: Free-air gravity disturbance for Block CS05 with respect to the WGS-84 ellipsoid.

## 4. Data Usage Guidelines

### 4.1 Suggested Data Handling

This data product was purposefully filtered to preserve the amplitude of the long-wavelength gravity signal. As a trade-off, the filter allows some short wavelength noise to remain in the product. Prior to use for geophysical purposes, the data should be run through a frequency-domain low-pass filter to remove that excess short wavelength noise. For geodetic purposes, higher frequencies can be damped during inclusion into a spherical harmonic model. In any case where downward continuation will be done with this data, the high frequency noise should first be filtered out, damped, or otherwise dealt with so that the downward continuation does not amplify the noise.

### 4.2 Documentation

The survey block User Manual, the general GRAV-D User Manual, and metadata for the block should all be downloaded with the data and kept in the same directory. The contents of the manuals are critical to correctly understanding the quality of the data and using the data properly.

### 4.3 How to Cite These Data

The following citations should be used in all presentations or publications that reference the GRAV-D work. Please replace the *DATE* tag in the following references with the date you downloaded the data or reports from the NGS website.

The GRAV-D Team, in alphabetical order, are: Vicki A. Childers, Justin E. Dahlberg, Theresa M. Damiani, Sandra A. Martinka Preaux, Carly A. Weil, Tim G. Wilkins, and Monica A. Youngman.

To reference the CS05 data file, reference the webpage:

GRAV-D Team (2015). "Gravity for the Redefinition of the American Vertical Datum (GRAV-D) Project, Airborne Gravity Data; Block CS05". Available *DATE*. Online at: [http://www.ngs.noaa.gov/GRAV-D/data\\_CS05.shtml](http://www.ngs.noaa.gov/GRAV-D/data_CS05.shtml)

To reference the block and survey details, reference the block user manual:

GRAV-D Team (2015). "Block CS05 (Eastern South 03); GRAV-D Airborne Gravity Data User Manual." Monica Youngman, Carly Weil, and Timothy Salisbury, ed. Version BETA. Available *DATE*. Online at: [http://www.ngs.noaa.gov/GRAV-D/data\\_CS05.shtml](http://www.ngs.noaa.gov/GRAV-D/data_CS05.shtml)

To reference the general GRAV-D project operations, reference the General User Manual:

GRAV-D Team (2013). "GRAV-D General Airborne Gravity Data User Manual." Theresa Damiani and Monica Youngman, ed. Version 2. Available *DATE*. Online at: [http://www.ngs.noaa.gov/GRAV-D/data\\_CS05.shtml](http://www.ngs.noaa.gov/GRAV-D/data_CS05.shtml)

## 5. References

Micro-g LaCoste, 2010. "TAGS Turnkey Airborne Gravity System AIR III Hardware & Operations Manual."