

Block ES05 (Eastern South 05)

GRAV-D Airborne Data Release User Manual

Applies to Data BETA Release, 10/2016

Edited by Monica A. Youngman, Carly A. Weil and Timothy D. Salisbury

Introduction to GRAV-D and Data User Manuals

NOAA's National Geodetic Survey (NGS) launched the Gravity for the Redefinition of the American Vertical Datum (GRAV-D) program in 2007. This program is designed to replace the current national vertical datum (NAVD 88) with a datum based upon a gravimetric geoid by 2022. To produce the geoid with 1-2 cm accuracy (where possible), an airborne campaign has been launched to measure the gravity field over all of the US and its holdings.

A more comprehensive description of the GRAV-D project is available in the "GRAV-D General Airborne Gravity Data User Manual." The version of that manual that applies to this release is manual v. 2.X. That manual also describes general details of the nominal airborne field operations, data post-processing software specifics, data naming schemes and distribution, data formats, and how to calculate other commonly-used gravity values from the released data. This manual relates details for this block of data that are in addition to the General User Manual.

GRAV-D uses some specific terminology (e.g. "block" for a geographic area with enough flown data and tie lines to provide error statistics, and "survey" for an occupation by the field team of a particular airport, at a particular time, and with a particular aircraft and instrument suite). For a full list of terminology, refer to the Glossary in the Appendices of the "GRAV-D General Airborne Gravity Data User Manual."

Contents

Introduction to GRAV-D and Data User Manuals	1
Figure List	3
Table List	3
1. Block Description	4
2. Survey Design and Execution	5
2.1 GPS/IMU Instrumentation.....	7
2.2 Gravity Instrumentation.....	7
3. GPS and Gravity Data Processing	8
3.1 Whole-Survey Applicable Details.....	8
3.1.1 GPS	8
3.1.2 Ground Gravity Tie.....	8
3.1.3 Gravity Filtering.....	9
3.2 Whole-Block Applicable Details	9
3.2.1 Gravity Error Analysis	9
3.3 Flight- and Line-Specific Details	12
3.3.1 GPS processing- by flight.....	12
3.3.2 Gravity processing- by line	12
4. Data Usage Guidelines	18
4.1 Suggested Data Handling.....	18
4.2 Documentation	18
4.3 How to Cite These Data.....	18
5. References	18

Figure List

Figure 1: Google Earth Image of the Location of Block ES05 (black rectangle).	4
Figure 2: Data Coverage for ES05.....	6
Figure 3: Crossover Residuals, Histogram, and Statistics for Block ES05.	11
Figure 4: Full-field gravity at altitude (mean removed) for Block ES05.	16
Figure 5: Free-air gravity disturbance for Block ES05 with respect to the WGS-84 ellipsoid. ..	17

Table List

Table 1: Latitude and Longitude Coordinates of Corner Points Defining Block ES05.....	4
Table 2: Survey Overview	5
Table 3: Aircraft and Instrumentation	5
Table 4: Survey Design and Execution	5
Table 5: Lever Arm Measurements FROM the Center of the Gravimeter's Sensor TO the Other Instruments	7
Table 6: Lever Arm Measurements FROM the SPAN TO the GPS Antenna	7
Table 7: GPS High Rate Data Availability (1 Hz or higher).....	8
Table 8: Gravity Crossover Error Analysis	9
Table 9: Quality of Cross Lines Used in Crossover Analysis.....	11
Table 10: Average Data Line Correlation.....	12
Table 11: GPS+IMU and GPS-only Kinematic Processing Results.....	13
Table 12: Gravity Processing Results.....	14
Table 13: Bias from EGM08 by Line	15

1. Block Description

GRAV-D Block **ES05** is located in the **E**astern Time Zone, in the **S**outh half (south of 40° latitude). This was the fifth (**05**) block of data completed in that region. Block ES05 is about 430 km by 520 km over the Atlantic and Florida ([Figure 1](#)). The corner coordinates defining Block ES05 are listed in [Table 1](#).




Figure 1: Google Earth Image of the Location of Block ES05 (black rectangle).

Table 1: Latitude and Longitude Coordinates of Corner Points Defining Block ES05

Latitude (decimal degrees)	Longitude (decimal degrees)
-80.84301909	31.10998946
-81.02077520	27.33609436
-76.11248098	27.00723587
-75.59126606	30.58211599
-80.84301909	31.10998946

2. Survey Design and Execution

Airborne gravity data in Block ES05 were collected during two surveys: FL15-1 (Florida 2015 first occupation) and FL15-2 (Florida 2015 second occupation). All data and cross flights were done at 20,000 ft with the same aircraft and instrument suite. Supplementary data from transit (target of opportunity) flights may be made available at a future date. [Table 2](#), [Table 3](#), and [Table 4](#) give a synopsis of survey layout and execution for the data. [Figure 2](#) shows the data coverage, plotted in Google Earth.

In the ES05 all data lines are East-West and cross lines North-South. The block consists of 39 data lines, 5 cross lines. The usual line numbering scheme used by GRAV-D (see “General User Manual”) was used for this survey. In the data file, line numbers are preceded by the block name (i.e. ES05101= block ES05’s line 101).

Table 2: Survey Overview

Conducting Organization	NOAA- National Geodetic Survey	
Survey Name	FL15-1	FL15-2
Airport Base of Operations	New Smyrna Beach Municipal Airport (KEVB) AirGate Aviation FBO 2022 Aero Circle New Smyrna Beach, FL 32168	
Geographic Location	Florida	
Dates of Airborne Operations	Jan 15 th – May 3 rd 2015	Dec 11 th 2015 – April 1 st 2016

Table 3: Aircraft and Instrumentation

Aircraft	Cessna 441 Conquest II
Engines, number and type	2, Turboprop
Gravity Instrumentation	Micro-g LaCoste (MGL) TAGS S-161 (relative) MGL A-10 25 (absolute) MGL D-43, G-6 (relative)
GPS Instrumentation	NovAtel DL-4 Plus NovAtel SPAN-SE (GPS + IMU)

Table 4: Survey Design and Execution

Line Spacing	Data Lines: 10 km Cross Lines: ~80 km
Type of Layout	Regular data lines & regular cross lines
Nominal Survey Altitude	20,000 ft
Nominal Aircraft Ground Speed	~250 knots
Number of Lines Released	Data Lines: 47 Cross Lines: 6 Repeat Lines: 0
Number of Crossovers	226




Figure 2: Data Coverage for ES05. Data lines start in the north at 101 and continue south to 144. Airports marked with red star.

2.1 GPS/IMU Instrumentation

The Cessna 441 Conquest II had one GPS antennas available for scientific measurements. Two geodetic-quality GPS receivers shared the antenna: NovAtel DL-4 Plus (included as part of the TAGS gravimeter timing unit) and a NovAtel (inside the SPAN-SE system). The NovAtels had a data rate of 1 Hz and the SPAN NovAtel of 20Hz. The NovAtel μ IMU system also contained an Inertial Measurement Unit (IMU) that recorded aircraft orientation information at 200 Hz during the flight, including pitch, roll, yaw, and heading.

On the ground, two Ashtech Z-Surveyors recorded at 1 Hz and served as GPS base stations throughout the survey. See Section [3.2.1](#) for a table of GPS data available for each flight and processing details.

2.2 Gravity Instrumentation

The Micro-g LaCoste TAGS (Turn-key Airborne Gravimetry System) was mounted in the cargo area. The TAGS records data at 1Hz and has a NovAtel timing unit mounted on the gravimeter. The gravimeter also records an environmental file at 0.1 Hz. For more information on the instrument, refer to its user manual (Micro-g LaCoste, 2010).

The IMU was mounted on top of the TAGS and in the center of the frame. [Table 5](#) lists the lever arm measurements between the TAGS and other instruments (distances are measured along the body of the aircraft: X positive toward the nose, Y positive toward the right, and Z positive down.) [Table 6](#) lists the lever arm measurement between the TAGS and the SPAN-SE (distances measured along the body of the aircraft: X positive toward the right, Y positive toward the nose, and Z positive up).

Table 5: Lever Arm Measurements FROM the Center of the Gravimeter's Sensor TO the Other Instruments

Instrument/Location	X (m)	Y (m)	Z (m)
NovAtel SPAN-SE IMU	-0.016	-0.01	0.476

Table 6: Lever Arm Measurements FROM the SPAN TO the GPS Antenna

Instrument/Location	X (m)	Y (m)	Z (m)
GPS Antenna	0.127	-1.39	0.408

3. GPS and Gravity Data Processing

3.1 Whole-Survey Applicable Details

3.1.1 GPS

Table 7: GPS High Rate Data Availability (1 Hz or higher)

Airport	Type	Receiver	Flight Available	2015-2016 Day of Year Available
FL15-1	Kinematic	NovAtel (0013)	F01-F29	20, 22, 29, 32, 37-39, 42, 83, 88-91, 93, 95-101, 112-113, 122-123
		NovAtel (SPAN)	F01-F29	20, 22, 29, 32, 37-39, 42, 83, 88-91, 93, 95-101, 112-113, 122-123
	Static	Ashtech 1EVB	F01-F29	20, 22, 29, 32, 37-39, 42, 83, 88-91, 93, 95-101, 112-113, 122-123
		Ashtech 2EVB	F01-F29	20, 22, 29, 32, 37-39, 42, 83, 88-91, 93, 95-101, 112-113, 122-123
FL15-2	Kinematic	NovAtel (0013)	F01-F30	353, 4, 11, 18-20, 25, 30, 33, 37, 43-45, 51, 58, 66-68, 71, 75, 83
		NovAtel (SPAN)	F01-F30	353, 4, 11, 18-20, 25, 30, 33, 37, 43-45, 51, 58, 66-68, 71, 75, 83
	Static	Ashtech 1EVB	F01-F30	353, 4, 11, 18-20, 25, 30, 33, 37, 43-45, 51, 58, 66-68, 71, 75, 83
		Ashtech 2EVB	F01-F30	353, 4, 11, 18-20, 25, 30, 33, 37, 43-45, 51, 58, 66-68, 71, 75, 83

Data were processed using WGS84 and ITRF08 with precise point positioning. Average position accuracy for the data block is calculated from the final GPS position solution. Position standard deviation is estimated by the GPS processing programs for each flight and those numbers are averaged to provide a survey-wide estimate of GPS position accuracy. For the data lines, the average horizontal position accuracy is 0.0314 m and the average vertical position accuracy is 0.0162 m.

3.1.2 Ground Gravity Tie

Absolute gravity measurements were performed by NGS with a Micro-g LaCoste A-10 gravimeter in January, 2015. At the airports the A-10 was set up at the exact location of the aircraft. The positions were determined from the GPS collected during the gravity survey while the plane was parked. In New Smyrna, FL the location is designated as KEVB TAGS (29.05725°N , 80.94329°W) and it has an absolute gravity value of 979259.235± 0.00806 mGal at 159.385 cm above the tarmac.

3.1.3 Gravity Filtering

Newton v1.2 uses a time-domain Gaussian filter that is applied three times to the data during final filtering. The Gaussian filter chosen for this survey has a 6-sigma of 120s, i.e. a 2-sigma of only 40s. Applying the filter three times provides superior noise reduction compared to a single application of the filter. Although the triple application provides better noise reduction, the filter is tailored to best preserve the amplitudes of the long wavelength signal, while allowing some short wavelength noise to remain in the final product. For suggestions on data handling, including on further noise suppression, see Section [4.1 Suggested Data Handling](#).

3.2 Whole-Block Applicable Details

3.2.1 Gravity Error Analysis

Crossover error analysis was done by identifying the crossing points of the data lines and cross lines and then applying the standard free-air correction to bring all points to the average altitude of the block. There was an unidentified bias in all flight lines, so an additional correction was applied before the crossover analysis to adjust each line's median airborne gravity value to the median gravity value of EGM08 along the line. The bias-corrected difference between the cross line gravity value and data line gravity value is the residual. The square root of the RMS of the residuals yields the total RMS error. For ES05, the result of the crossover analysis is shown in [Table 8](#) and in [Figure 3](#).

Table 8: Gravity Crossover Error Analysis

Nominal Altitude (ft)	Nominal Altitude (m)	Altitude for Analysis (m)	Number of Crossovers	RMS Of Residuals (mGal)	Std. Dev. Of Residuals (mGal)	Mean Crossover Difference (mgal)	RMS Error (mGal)
20,000	6,069	6,153	226	3.58	3.55	0.52	2.53

One assumption of crossover analysis is that the quality of the cross lines are high and that the crossover difference reflects only the error in the data lines. This is not necessarily the case. This means that the crossover statistics do not accurately reflect the quality of the data lines, due to the errors in the cross lines. One way to quantify this problem is by reporting the standard deviation and mean of the crossover residuals for each cross line, as in [Table 9](#). The higher the standard deviation of the residuals, the more likely that the cross line was noisy. Also, a non-zero mean could indicate a cross-line bias with respect to the data lines (unlikely here because of the bias correction applied), which would produce false crossover statistics that indicate poor data line quality.





Figure 3: Crossover Residuals, Histogram, and Statistics for Block ES05. Color scale in mGals.

Table 9: Quality of Cross Lines Used in Crossover Analysis

Cross Line Number	Standard Deviation of Residuals Along Line (mGal)	Mean of Residuals Along Line (mGal)
601	2.35	-1.52
502	3.22	1.44
602	2.54	3.21
503	2.59	-1.42
504	2.99	3.47
505	3.29	-0.91

Another way to evaluate the quality of gravity data is to calculate the correlation of the gravity values along two adjacent data lines. Average correlation and statistics on the spread of correlations can yield information about the quality of the data lines ([Table 10](#)). This technique works well as a measure of data quality in areas with little lateral variability in the gravity field (such as the Gulf of Mexico). But the technique doesn't work well when the correlations are not expected to be high, such as in areas with large changes in topography and/or density from data line to data line. Line correlations were calculated for adjacent lines and then averaged to give an overall quality measurement. Correlations > 80% mean the lines are very highly correlated, 70% - 80% mean the lines are highly correlated, 50% - 70% mean the lines are more correlated than not, and <50% are more uncorrelated than correlated.

Table 10: Average Data Line Correlation

Number of Correlations	Average Data Line Correlation	Standard Deviation of Correlations
26	96.90%	4.84%

A fourth way of gauging data quality is by calculating the repeatability of the gravity signal along reflight lines of good quality. Reflight analysis can also help to pinpoint the lightest filtering that produces highly-correlated results.

3.3 Flight- and Line-Specific Details

3.3.1 GPS processing- by flight

GPS data were processed in Inertial Explorer (IE) 8.6. A lever arm correction (to move the position solution from that of the GPS antenna to that of the center of the gravimeter) was applied within the IE software and included in the GPS+IMU solution. In the case of the GPS-only solution, no IMU data were available and a translation-only, vertical lever arm correction was instead applied by the Newton gravity code to translate the GPS-only positions to the center of the gravimeter.

NGS has developed an independent method of measuring the quality of GPS position solutions based on information available from IE. For the GPS-only part of the position solution, the quality analysis takes into account the following: whether a fixed or float solution was achieved, the magnitude of the combined separation between forward and reverse solutions (a measure of precision), and the estimated position accuracy. For details on the calculation, please refer to the “GRAV-D General Airborne Gravity Data User Manual.”

3.3.2 Gravity processing- by line

All gravity processing was done with NGS’ Newton v1.2 software. For a description of the package, refer to the “GRAV-D General Airborne Gravity Data User Manual.” The final gravity data file contains full-field gravity at altitude ([Figure 4](#)), although other gravity products such as free-air anomalies or free-air disturbances ([Figure 5](#)) can be easily calculated by following directions in Section 4 of the “GRAV-D General Airborne Gravity Data User Manual”.

Table 11: GPS+IMU and GPS-only Kinematic Processing Results

Survey	Flight Num.	Rover GPS Unit	Solution Type	Elevation Mask (degrees)	Line Num.	NGS Quality Grade
FL15-1	1	SPAN	GPS+IMU	5	143	100.00
					144	100.00
	2	SPAN	GPS+IMU	7.5	141	100.00
					142	100.00
	3	SPAN	GPS+IMU	7.5	139	100.00
	8	SPAN	GPS+IMU	7.5	135	99.85
					136	100.00
	9	SPAN	GPS+IMU	7.5	133	100.00
					134	100.00
	10	SPAN	GPS+IMU	5	438	100.00
	11	SPAN	GPS+IMU	5	131	100.00
					132	100.00
	12	SPAN	GPS+IMU	5	337	100.00
					434	100.00
	13	SPAN	GPS+IMU	5	129	100.00
					130	100.00
	15	SPAN	GPS+IMU	7.5	128	100.00
	16	SPAN	GPS+IMU	5	503	100.00
					601	100.00
	17	SPAN	GPS+IMU	7.5	126	100.00
					227	100.00
	18	SPAN	GPS+IMU	7.5	124	100.00
					125	100.00
	19	SPAN	GPS+IMU	5	122	100.00
					123	100.00
	20	SPAN	GPS+IMU	5	120	100.00
					121	100.00
	21	SPAN	GPS+IMU	7.5	118	100.00
					119	100.00
	22	SPAN	GPS+IMU	7.5	117	100.00
	24	SPAN	GPS+IMU	7.5	214	100.00
					215	100.00
	27	SPAN	GPS+IMU	5	113	100.00
					212	100.00
	28	SPAN	GPS+IMU	7.5	440	100.00
					505	100.00
	29	SPAN	GPS+IMU	7.5	111	100.00
					316	100.00
FL15-2	2	SPAN	GPS+IMU	5	409	62.04
					410	93.80
	3	SPAN	GPS+IMU	5	107	100.00
					108	95.49
	17	SPAN	GPS+IMU	7.5	106	100.00
	22	SPAN	GPS+IMU	5	104	98.99
	23	SPAN	GPS+IMU	7.5	203	100.00
					305	100.00
	28	SPAN	GPS+IMU	7.5	101	98.78
					202	100.00
	29	SPAN	GPS+IMU	5	303	84.36
					502	98.84
					504	73.87
	30	SPAN	GPS+IMU	7.5	302	76.08
					602	91.32

Table 12: Gravity Processing Results

Survey	Flight Num.	Line Num.	Times of Deleted Data Section(s)
FL15-1	1	143	
		144	
	2	141	
		142	
	3	139	
	8	135	
		136	
	9	133	
		134	
	10	438	
	11	131	
		132	
	12	337	
		434	
	13	129	
		130	
	15	128	
	16	503	
		601	
	17	126	
		227	
	18	124	
		125	
	19	122	
		123	
	20	120	
		121	
	21	118	
		119	
	22	117	
	24	214	
		215	
	27	113	
		212	
	28	440	
		505	
	29	111	
		316	
FL15-2	2	409	
		410	
	3	107	
		108	
	17	106	
	22	104	
	23	203	
		305	
	28	101	
		202	
	29	303	
		502	
		504	
	30	302	
		602	

Table 13: Bias from EGM08 by Line

Survey	Flight Num.	Line Num.	Bias from EGM08
FL15-1	1	143	60.15
		144	63.05
	2	141	61.99
		142	64.95
	3	139	61.99
	8	135	59.12
		136	62.00
	9	133	59.65
		134	63.74
	10	438	64.08
	11	131	62.31
		132	58.36
	12	337	62.52
		434	58.66
	13	129	63.07
		130	59.59
	15	128	62.41
	16	503	60.68
		601	60.64
	17	126	64.57
		227	59.94
	18	124	59.78
		125	63.24
	19	122	62.58
		123	59.42
	20	120	62.76
		121	58.86
	21	118	59.04
		119	62.48
	22	117	62.28
	24	214	64.15
		215	59.01
	27	113	63.12
		212	60.44
	28	440	59.80
		505	60.82
	29	111	59.79
		316	62.26
FL15-2	2	409	61.91
		410	65.85
	3	107	91.70
		108	64.86
	17	106	61.52
	22	104	60.69
	23	203	62.43
		305	64.79
	28	101	65.59
		202	68.73
	29	303	61.53
		502	63.90
		504	65.17
	30	302	61.89
		602	64.16




Figure 4: Full-field gravity at altitude (mean removed) for Block ES05. This is the data in the gravity release ".txt" file and includes the effects of differing altitudes along flight lines.




Figure 5: Free-air gravity disturbance for Block ES05 with respect to the WGS-84 ellipsoid.

4. Data Usage Guidelines

4.1 Suggested Data Handling

This data product was purposefully filtered to preserve the amplitude of the long-wavelength gravity signal. As a trade-off, the filter allows some short wavelength noise to remain in the product. Prior to use for geophysical purposes, the data should be run through a frequency-domain low-pass filter to remove that excess short wavelength noise. For geodetic purposes, higher frequencies can be damped during inclusion into a spherical harmonic model. In any case where downward continuation will be done with this data, the high frequency noise should first be filtered out, damped, or otherwise dealt with so that the downward continuation does not amplify the noise.

4.2 Documentation

The survey block User Manual, the general GRAV-D User Manual, and metadata for the block should all be downloaded with the data. The contents of the manuals are critical to correctly understanding the quality of the data and using the data properly.

4.3 How to Cite These Data

The following citations should be used in all presentations or publications that reference the GRAV-D work. Please replace the *DATE* tag in the following references with the date you downloaded the data or reports from the NGS website.

The GRAV-D Team, in alphabetical order, are: Vicki A. Childers, Justin E. Dahlberg, Theresa M. Damiani, Sandra A. Martinka Preaux, Timothy D. Salisbury, Carly A. Weil, Tim G. Wilkins, and Monica A. Youngman.

To reference the ES05 data file, reference the webpage:

GRAV-D Team (2014). "Gravity for the Redefinition of the American Vertical Datum (GRAV-D) Project, Airborne Gravity Data; Block ES05". Available *DATE*. Online at: http://www.ngs.noaa.gov/GRAV-D/data_ES05.shtml

To reference the block and survey details, reference the block user manual:

GRAV-D Team (2014). "Block ES05 (Eastern South 03); GRAV-D Airborne Gravity Data User Manual." Monica Youngman, Carly Weil, and Tim Salisbury, ed. Version BETA. Available *DATE*. Online at: http://www.ngs.noaa.gov/GRAV-D/data_ES05.shtml

To reference the general GRAV-D project operations, reference the General User Manual:

GRAV-D Team (2013). "GRAV-D General Airborne Gravity Data User Manual." Theresa Damiani and Monica Youngman, ed. Version 2. Available *DATE*. Online at: http://www.ngs.noaa.gov/GRAV-D/data_ES05.shtml

5. References

Micro-g LaCoste, 2010. "TAGS Turnkey Airborne Gravity System AIR III Hardware & Operations Manual."